

UNCLASSIFIED

AD NUMBER
AD467513
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; Nov 1964. Other requests shall be referred to U.S. Army Foreign Science and Technology Center, Charlottesville, VA.
AUTHORITY
OCRD D/A ltr, 28 Mar 1968

THIS PAGE IS UNCLASSIFIED

SECURITY

MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.

Separate page printouts MUST be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

FOR OFFICIAL USE ONLY

U. S. ARMY MATERIEL COMMAND

FSTC 381-T64-36


TRANSLATION

MOIST THERMAL METHOD FOR DISINFECTING
CONTAINERS

U S ARMY
FOREIGN SCIENCE
AND
TECHNOLOGY
CENTER

DDC
RECEIVED
DEC 1 1964
DDC-IRA B

November 1964



FOR OFFICIAL USE ONLY

RECEIVED BY: DDC
AD No. 467513

This translation is a rendition of the original foreign text without any analytical or editorial comment. Statements or theories advocated or implied are those of the source and do not necessarily reflect the position or opinion of the U.S. Army Foreign Science and Technology Center.

Approved

G. M. PAYNE
Colonel, G.S.
Deputy Commander

Requests for additional copies of this document should be directed to the Commanding Officer, Attn: AMXST-SD at the address below.

U. S. ARMY FOREIGN SCIENCE AND TECHNOLOGY CENTER
Munitions Building
Washington, D. C. 20315

381-T64-36

Moist Thermal Method for Disinfecting
Containers

by

F. T. LISITSYN

and

F. M. SIYANITSKIY

English Pages: 4

Source: ZASHCHENIYE RASTENIY OT VREDITELEY I BOLEZNEY
(Russian)
Vol. 5, No. 3, pp. 48-49

FOR OFFICIAL USE ONLY

MOIST THERMAL METHOD FOR DISINFECTING CONTAINERS

Numerous cases are known in which quarantined pests have been spread with containers in which agricultural products were shipped.

Oriental fruit moths, Mediterranean fruit flies, large mandarin flies, and certain other dangerous fruit pests have been discovered repeatedly in quarantine inspections in which imported goods arriving in wooden boxes were examined. If such containers were utilized for household purposes without previous disinfection, they could become sources for spreading pests through the country.

One may judge how great this danger is by the data from our quarantine inspection service -- the total number of boxes remaining after the sale of fruit in the city of Leningrad alone is in the hundreds of thousands.

After several years of research, the Leningrad Quarantine Laboratory discovered a simple, cheap, and very effective method for disinfecting boxes -- in boiling water.

In 1959 more than 170,000 boxes which had contained Chinese and Korean apples were processed in this way in the fruit sales bases of Lengorplodoovoshch [Leningrad City Vegetable and Fruit Administration]. The results were good.

The method we proposed was approved and established as the standard by the State Inspection Service for Quarantine of Agricultural Plants of the Ministry of Agriculture USSR throughout the RSFSR in instances where there is no chamber for chemical processing of containers.

Stationary or mobile facilities with rectangular or semi-cylindrical boilers which make use of furnaces or superheated steam to heat the water can be utilized for disinfecting boxes in boiling water.


The length of the boiler is 2.5 m, its width 0.9 m, and its depth 0.7 m. It is made by welding sheet steel 3 to 4 mm thick to a framework

of 40 x 40 mm angle iron. The same sort of angle iron is used for making double guiding slide rails for delivering boxes and holding them in the water.

Six to eight standard boxes can be immersed at intervals of 8 - 10 seconds in a boiler of this length. The boxes can be moved from under the guide rails to the surface of the water and removed from the boiler at the same rate. Thus, every box is immersed in boiling water for 40 to 60 seconds and completely disinfected within this interval.

This apparatus is handled by two persons. Conveys or roller conveyors can be set up to lighten the delivery of boxes to the boiler and to more them to the stacking area after disinfection.


Plan



Plan of a stationary facility with furnace heating

1 - shed pillars; 2 - roller conveyors; 3 - boiler; 4 - upper guide rails; 5 - lower guide rails; 6 - firebox; 7 - platform for loading boxes; 8 - steps; 9 - smokestack; 10 - valve for draining water; 11 - place for fastening the lower guide rails to the side of the boiler; 12 - place for fastening the upper guide rails to the side of the boiler.


Cross section through II-II



Longitudinal cross section of the facility

1 - shed pillar; 2 - brickwork; 3 - boiler; 4 - upper guide rails; 5 - lower guide rails; 6 - boxes under processing (shown by dashed lines); 7 - firebox; 8 - platform for loading boxes; 9 - steps; 10 - stone foundation.

Cross section through I-I



Transverse cross section of the facility

1 - open shed; 2 - tar paper roof; 3 - boiler; 4 - upper guide rails; 5 - lower guide rails; 6 - smokestack; 7 - firebox; 8 - brickwork; 9 - stone foundation.